



**WHERE
PRECISION
DRIVES
PRODUCTION**



SCANNER SPECIFICATIONS

Light Source

High output LEDs

Decodes/Second

Up to 45

Working Distance

40 mm - 105 mm (1.57 in - 4.13 in)

Interface

USB

Available Codes

1-D barcodes: Codabar, Code 39, Code 128, Code 93, Code 25, Interleaved 2 of 5, Pharma, Postal, Code UPC/EAN/JAN, MSI

2-D barcodes: Data Matrix™ (IDMax and IDQuick: ECC 0, 50, 80, 100, 140 and 200) QR Code and microQR Code, RSS/CS, PDF 417, MicroPDF 417, AztecCode, DotCode, MaxiCode

Barcode Reader

PVA-BC | Mounted Intelligent ID Manager

PVA barcode readers are best in class ID readers, offering superior performance with the latest ID tools, flexibility to configure the reader in terms of lighting and optics to optimize the application. An ease-of-use gives the user the ability to setup and deploy an application quickly and efficiently.

PVA's high speed mini imager has many integrated features including:

- Decodes linear bar codes and 2D symbols omnidirectionally in moving applications at speeds over 100 mm per second (3.94 in/sec)
- Compact 42.4 mm (1.67 in) by 26.5 mm (1.04 in) by 35.8 mm (1.4 in) profile
- Profile illuminated LEDs on top of scanner provide visual confirmation of the scanner performance
- Flexible mounting on conveyor or robot
- CE mark and NRTL and FCC Class A compliant

For more information, please contact PVA at info@pva.net or (518) 371-2684.

