



**WHERE  
PRECISION  
DRIVES  
PRODUCTION**



## SYSTEM SPECIFICATIONS

### Dimensions

139.7 mm x 69.22 mm x 25.56 mm  
(5.5 in x 2.73 in x 1.40 in)

### Weight

9 oz (0.26 kg)

### Viscosity Range

25,000 cps – Paste

### Minimum Shot Size (Filled Material)

0.020" (0.5 mm) Dots

### Maximum Inlet Fluid Pressure

100 psi

### Auger Material

Carbide

### Auger Motor

24V DC Servo Motor

## SV200 Auger Valve

The SV200 Auger Valve is ideal for dispensing 2-part, premixed epoxies and pastes in dot and bead patterns. The SV200 can dispense dots as small as 0.020" in diameter and features a quick release to separate the motor assembly from the auger for easy cleaning of entire fluid path. The SVC100 Servo Controller provides customized valve settings for handheld or automated applications.

The SV200 has many integrated features including:

- The choice of an 8 or 16 pitch carbide auger for custom profiles
- 3, 5, 10, or 30 cc syringe barrel inserts
- Quick release for easy cleaning
- Disposable feed tube connects syringe to the fluid body
- Virtually zero dead space within the valve design
- Field maintainable design
- 24V DC servo motor drive with optional encoder to provide displacement feedback
- Adjustable auger speed and reverse motion for clean cycle stops

For more information please contact one of our sales representatives at (518) 371-2684.



# SV200 Mounting Dimensions

